

Carrier Boards

CRX-S32G

miriac® MPX-S32G274A



Highlights



- 1x 1000BASE-T1
- 6x 100BASE-T1







NXO Gold Partner



Product Description

Find out more about our CRX-S32G below:



Features


Ethernet	
1GbE:	4x
1000BASE-T1:	1x
100 Mb:	1x
100BASE-T1:	6x
TSN / IEEE 1588:	Yes
High Speed IO	
USB 2.0:	1x
miniUSB:	1x
Software / Additional	
miniPCle:	1x
M.2:	1x (type M)


General Note:

Our standard product versions offer what we consider to be the optimum configuration in terms of performance, price, usage and TDP. The product features lists specify the maximum range of functions per interface. However, not all interfaces or functions are always available in parallel. Flexible SERDES multiplexing is one of the reasons for this. In addition, we provide multiple memory expansion options and are also happy to accommodate specific customer wishes. So do not hesitate to contact us directly to discuss your desired configuration.

www.microsys.de 2 | 4

Block Diagrams





www.microsys.de 3 | 4



Name Description Image

miriac® MPX-S32G274A Vehicle gateway platform with massive native CAN support



miriac® MPX-S32G399A MicroSys' 2nd Gen of Sys

MicroSys' 2nd Gen of System-on-Modules for vehicle networks based on the NXP® S32G399A processor





Mühlweg 1 82054 Sauerlach Germany Sales: +49 8104 801-130 E-Mail: info@microsys.de www.microsys.de

