


Carrier Boards

CRX07-TSN

Fits our Layerscape® Family Member:

mirrac@MPX-LS1028A



Highlights

- 1x Display Port
- 5x 1GbE TSN / IEEE 1588
- 2x USB 3.0





Product Description

Find out more about our CRX7-TSN below:



Features


Graphic	
HDMI Interface:	1x DisplayPort
Ethernet	
TSN:	Y
TSN / IEEE 1588:	5x Gbit TSN
High Speed IO	
USB 3.0:	2x
miniUSB:	1x debug
µUSB:	1x debug
Operating Condition	
Reset Push Button:	Yes
Operating Condition	
Power Supply Voltage:	Single 9 to 24 V DC input supply voltage range
Mechanical	
Dimensions:	160 mm x 100 mm
Software / Additional	
miniPCle:	2x
mSATA:	1x

General Note:

Our standard product versions offer what we consider to be the optimum configuration in terms of performance, price, usage and TDP. The product features lists specify the maximum range of functions per interface. However, not all interfaces or functions are always available in parallel. Flexible SERDES multiplexing is one of the reasons for this. In addition, we provide multiple memory expansion options and are also happy to accommodate specific customer wishes. So do not hesitate to [contact us](#) directly to discuss your desired configuration.



Related Products

Name	Description	Image
miriac® MPX-LS1028A	Compact SoM with TSN, security engine and HMI	



Mühlweg 1
82054 Sauerlach
Germany

Sales: +49 8104 801-130
E-Mail: info@microsys.de
www.microsys.de

